

# 4Way Screenwall Electrimask

---

Horizontal and vertical masking panels provide the ultimate flexibility to view aspect ratios ranging from 1.33:1 to 2.35:1



# 4Way Screenwall Electrimask

Stewart's 4Way Screenwall Electrimask features both horizontal and vertical masking, providing the ultimate flexibility in aspect ratios. Combining a fixed screenwall with three individually motorized masking panels, this screen allows for any aspect ratio ranging from 1.33:1 to 2.35:1.

Optimize your 4Way Screenwall Electrimask with a variety of Stewart's award-winning front projection materials. Microperf X2 is available when acoustic transparency is required (acoustically transparent panels also available upon request).

Stewart's exclusive VeLux™ black-velvet appliqué gives the 4Way Screenwall Electrimask a luxurious look and feel. This specialized frame finish absorbs possible over-scan while boosting perceived contrast.



Horizontal panels drop down and rise up, while vertical panels drop down on either side to attain the desired aspect ratio.

## SPECIFICATIONS

Aluminum extrusion framing system	Included
Electronically controlled horizontal and vertical masking panels	Included
Specialized snap-fastening system	Included
VeLux™ appliqué finish	Included

## MATERIAL

Front projection material	Included
Rear projection material	Optional

## PERFORATIONS

Microperf X2 THX Ultra	Optional
Acoustically transparent masking panels	Optional

## MOUNTING

Wall mount brackets	Included
Aperture	Optional

## MASKING MOTOR

120 Volt	Included
220 Volt	Optional

## MASKING CONTROL

(2) High voltage wall switches (HVS) - horizontal panels	Included
(1) External 12 Volt trigger (VICS) - vertical panels	Included
BRIC - includes IR remote and keypad	Optional

## FRAME OUTER DIMENSIONS

Frame height	Image Height + 20" (508 mm)
Frame width	Image Width + 10" (254 mm)

For custom sizes and gains, please consult the WebSA or your local Stewart representative.

## Attainable Aspect Ratios: 1.78:1 » 2.35:1 » 1.85:1 » 1.33:1

Row	Model	Diagonal	Native Image		Frame Dimensions		Unit Weight
			Height	Width	Height	Width	
1	4WSN100H	100 (2540)	49 (1245)	87 (2210)	69 (1753)	97 (2464)	140 (63)
2	4WSN110H	110 (2794)	54 (1372)	96 (2438)	74 (1880)	106 (2692)	145 (65)
3	4WSN123H	123 (3124)	60 (1524)	107 (2718)	80 (2032)	117 (2972)	380 (171)
4	4WSN135H	135 (3429)	66 (1676)	118 (2997)	86 (2184)	128 (3251)	400 (180)

Row	NTSC (1.33:1)		Masked Image		Cinemascope (2.35:1)		Masked Image	
	Diagonal	Height	Width	Height	Diagonal	Height	Width	
1	82 (2083)	49 (1245)	65 (1651)	37 (940)	95 (2413)	41 (1041)	87 (2210)	
2	90 (2286)	54 (1372)	72 (1829)	41 (1041)	104 (2642)	41 (1041)	96 (2438)	
3	100 (2540)	60 (1524)	80 (2032)	45.5 (1156)	116 (2946)	45.5 (1156)	107 (2718)	
4	110 (2794)	66 (1676)	88 (2235)	50 (1270)	128 (3251)	50 (1270)	118 (2997)	