

Stealth Trapdoor

Ideal for concealing a projection screen in multi-purpose environments




Stealth Trapdoor

The Stealth Trapdoor was engineered for use within multi-purpose environments where the screen must disappear completely from sight when not in use.

The Stealth Trapdoor is available with a variety of Stewart's front or rear projection materials. Our exclusive Tab-Guy™ tensioning system ensures a smooth and completely flat screen surface. Matte black over-scan borders* provide a perfectly masked image area.

Microperf X2 and Cinemaparf options are available when acoustic transparency is required (acoustically transparent black drop available upon request).



SPECIFICATIONS:

Electronically controlled screen system with trapdoor	Included
Aluminum extrusion housing/case	Included
3-1/4 inch roller tube with insulated drive	Included
Exclusive Tab-Guy™ tensioning system	Included
Matte black over-scan border*	Included

SCREEN MATERIAL:

Front projection	Included
Rear projection	Optional

PERFORMANCES:

Microperf X2 THX Ultra	Optional
Cinemaparf	Optional
Acoustically transparent black drop only	Optional

MOUNTING:

Recessed/ceiling	Included
Adjustable drywall flanges	Included

SCREEN MOTOR:

120 Volt	Included
220 Volt	Optional

SCREEN CONTROL:

HVS (high voltage switch)	Included
LVC (low voltage switch control with 3 button wall switch)	Optional
STI (12V screen trigger interface)	Optional
IRR (IR remote)	Optional

CASE/HOUSING DIMENSIONS:

Case height	8.25 in (210mm)
Case depth	6.00 in (152mm)

*It is important to request only the amount of blackdrop required to ensure a picture perfect image.

For custom sizes and gains, please consult WebSA or your local Stewart representative.

HDTV Format - 1.78:1/16:9

Model	Image Diagonal	Image Height	Image Width	Max. Case Length	Batten Length	Unit Weight
SEL082H	82 (2083)	40.5 (1029)	72 (1829)	99 (2515)	84 (2134)	104 (47)
SEL092H	92 (2337)	45 (1143)	80 (2032)	107 (2718)	92 (2337)	112 (50)
SEL100H	100 (2540)	49 (1245)	87 (2210)	114 (2896)	99 (2515)	119 (54)
SEL106H	106 (2692)	52 (2337)	92.5 (4166)	191 (4851)	176 (4770)	125 (56)
SEL110H	110 (2794)	54 (1372)	96 (2438)	123 (3124)	108 (2743)	128 (58)

NTSC Format - 1.33:1/4:3

Model	Image Diagonal	Image Height	Image Width	Max. Case Length	Batten Length	Unit Weight
SEL060V	60 (1524)	36 (914)	48 (1219)	75 (1905)	60 (1524)	80 (36)
SEL072V	72 (1829)	43 (1092)	57 (1448)	84 (2134)	69 (1753)	89 (40)
SEL084V	84 (2134)	50 (1270)	67 (1702)	94 (2388)	79 (2007)	99 (45)
SEL090V	90 (2286)	54 (1372)	72 (1829)	99 (2515)	84 (2134)	104 (47)
SEL100V	100 (2540)	60 (1524)	80 (2032)	107 (2718)	92 (2337)	112 (50)

Cinemascope - 2.35:1

Model	Image Diagonal	Image Height	Image Width	Max. Case Length	Batten Length	Unit Weight
SEL091S	91 (2311)	36 (914)	84 (2134)	111 (2819)	96 (2438)	116 (52)
SEL105S	105 (2667)	41 (1041)	96.5 (2451)	123 (3124)	108 (2743)	128 (58)

Stewart
FILMSCREEN

RESIDENTIAL

Find your local representative at www.stewartfilmscreen.com/ reps